2012 OVERLAMINATE

Product Name	Film Type	Color	Film Thickness (mil)	Film + Adhesive Thickeness (mil)	Adhesive Type
3M Commercial Graphics, 800-328-3908, www.MyPRINTResource.com/10003398					
3M Scotchcal Gloss Film/Overlaminate IJ10-114	Non-cast Vinyl	Clear	3.1	3.6	Pressure-sensitive
3M Scotchcal Gloss Overlaminate 8508	Non-cast Vinyl	Clear	2.3	3.3	Pressure-sensitive
3M Scotchcal Gloss Overlaminate 8518	Cast vinyl	Clear	2	3	Pressure-sensitive
3M Scotchcal Gloss Overlaminate 8528	Cast vinyl	Clear	2	3	Pressure-sensitive
3M Scotchcal Gloss Overlaminate 8580	Ultra-conformable Cast vinyl	Clear	1	2.2	Pressure-sensitive
3M Scotchcal High Gloss Graffiti-Resistant Overlaminate 8912	Cast Polyester	Clear	1	2	Pressure-sensitive
3M Scotchcal High Gloss Overlaminate 639	Cast Polyester	Clear	1	1	Pressure-sensitive
3M Scotchcal Gloss Overlaminate 3640GPS	PVDF	Clear	1	2	Pressure-sensitive
3M Scotchcal High Gloss Overlaminate Film 3648*	Non-cast Vinyl	Clear	4	5	Pressure-sensitive
3M Scotchcal Luster Overlaminate 3619*	Cast vinyl	Clear	2	3	Pressure-sensitive
3M Scotchcal Luster Overlaminate 3645*	Cast vinyl	Clear	8	9	Pressure-sensitive
3M Scotchcal Luster Overlaminate 8519	Cast vinyl	Clear	2	3	Pressure-sensitive
3M Scotchcal Luster Overlaminate 8524	Non-cast Plastic	Clear	2	3	Pressure-sensitive
3M Scotchcal Luster Overlaminate 8908	Non-cast Polyolefin	Clear	2.5	3.5	Pressure-sensitive
3M Scotchcal Matte Overlaminate 3620*	Cast vinyl	Clear	2	2	Pressure-sensitive
3M Scotchcal Matte Overlaminate 3642GPS*	PVDF	Clear	1	2	Pressure-sensitive
3M Scotchcal Matte Overlaminate 3647*	Non-cast Vinyl	Clear	19	20	Pressure-sensitive
3M Scotchcal Matte Overlaminate 8509	Non-cast Vinyl	Clear	3	4	Pressure-sensitive
3M Scotchcal Matte Overlaminate 8520	Vinyl	Clear	2	3	Pressure-sensitive
3M Scotchcal Matte Overlaminate 8909	Non-cast Polyolefin	Clear	2.5	3.5	Pressure-sensitive
3M Scotchcal Optically Clear Overlaminate 8914*	Cast vinyl	Clear	1	2	Pressure-sensitive
3M Scotchcal Ultra-Matte Overlaminate 8915	Non-cast Vinyl	Clear	2	3	Pressure-sensitive
Scotchgard Graphic and Surface Protection Film 8991	Polyester	Clear	4	5	Pressure-sensitive
Scotchgard Removable Graphic and Surface Protection Film 8991R	Polyester	Clear	4	5	Pressure-sensitive
Advanced Grieg Laminators (AGL), 608-846-1025, www.MyPRINTResource.com/10003621					
Cover-Rite P3 G	Polyester		1	3	Copolymer
Cover-Rite P3 L	Polyester		0.5	3	Copolymer
Cover-Rite P3 M	Polyester		0.5	3	Copolymer
Cover-Rite P5 G	Polyester		3	5	Copolymer
Cover-Rite P5 eG	Polyester		2	5	Copolymer
Cover-Rite P5 L	Polyester		2	5	Copolymer
Cover-Rite P5 M	Polyester		3	5	Copolymer
Cover-Rite P5 T	Polyester		3	5	Copolymer
Cover-Rite P10 G	Polyester		7	10	Copolymer
Cover-Rite P10eG	Polyester		4	10	Copolymer
Cover-Rite P10 M	Polyester		7	10	Copolymer
Cover-Rite P10 T	Polyester		7	10	Copolymer
Cover-Rite V5T	Vinyl		4	5	Solvent Acrylic
Cover-Rite P3G DE (Dry Erase)	Polyester		0.75	3	Polyethylene
Cover-Rite P6 T	Embosed Composite		3	5	Copolymer
Cover-Rite V6G	Felxible Vinyl		4	6	Permanent Arcylic
Cover-Rite V6eG	Calendered PVC		4	6	Permanent Arcylic
Cover-Rite V6L	Felxible Vinyl		4	6	Permanent Arcylic
Cover-Rite V6eL	Calendered PVC		4	6	Permanent Arcylic
Cover-Rite V6M	Felxible Vinyl		4	6	Permanent Arcylic
Cover-Rite V6eM	Calendered PVC		4	6	Permanent Arcylic
Cover-Rite V6eTM	Calendered PVC		4	6	Permanent Arcylic
Cover-Rite V8eTM	Calendered PVC		5	8	Permanent Arcylic
Cover-Rite V6T	Vinyl		5	6	FG, Permanent Arcylic
Cover-Rite V4.75T	Vinyl		3.75	4.75	Permanent Arcylic
Cover-Rite V2G	Premium Cast Vinyl		2	2.5	Permanent Arcylic
Cover-Rite V2L	Premium Cast Vinyl		2	2.5	Permanent Arcylic
Cover-Rite V2M	Premium Cast Vinyl		2	2.5	Permanent Arcylic
Cover-Rite PC5T	Polyester		5	7	Solvent Acrylic
Cover-Rite PC10T	Polyester		10	12	Solvent Acrylic
Cover-Rite PC15T	Polyester		15	17	Solvent Acrylic
Cover-Rite PP1GDE (Dry Erase)	Polyester		1	1.5	Permanent Arcrylic

RESOURCE CHART

Release Liner	Activation Temp (°F)	Width(s)	Core Size (inches)	Finish	Ink Compatibility
Polycoated Paper	55°F	54 x 54 Y	3	Glossy	Inkjet
Kraft Paper	50°F	30/54/61 x 50/100/200 Y	3	Glossy	Inkjet; Electrostatic; Screen Print
Polyester	50°F	30/36/48/54/60 x 25/50/100Y *	3	Glossy	Inkjet
Polyester	50°F	54 x 25/50 Y	3	Glossy	Inkjet
Kraft Paper	50°F	54 x 25/50 Y	3	Glossy	Inkjet
Kraft Paper	60°F	49 x 54 Y	3	High Gloss	Inkjet; Electrostatic
Kraft Paper	50°F	24/48 x 50 Y*	3	High Gloss	Inkjet; Electrostatic
Kraft Paper	60°F	48 x 50 Y*	3	Glossy	Screen Print; Cut Graphics
Kraft Paper	50°F	48 x 50 Y*	3	High Gloss	Inkjet; Electrostatic; Screen Print
Kraft Paper	50°F	48/54/60 x 10/50 Y *	3	Luster	Inkjet
Kraft Paper	50°F	48/54 x 50 Y*	3	Luster	Inkjet; Electrostatic; Screen Print
Kraft Paper	50°F	36/48/54/60 x 25/50/100 Y *	3	Luster	Inkjet; Electrostatic
Kraft Paper	50°F	30 x 50 Y; 54 x 25/50 Y	3	Luster	Inkjet; Electrostatic
Kraft Paper	50°F	48 x 50 Y*	3	Luster	Inkjet; Electrostatic
Kraft Paper	50°F	48/54/60 x 10/50 Y *	3	Matte	Inkjet
Kraft Paper	60°F	48 x 50 Y*	3	Matte	Screen Print; Cut Graphics
Kraft Paper	50°F	48 x 50 Y*	3	Matte	Inkjet; Electrostatic; Screen Print
Kraft Paper	50°F	30/54/61 x 50/100/200 Y	3	Luster	Inkjet; Electrostatic; Screen Print
Kraft Paper	50°F	36/48/54/60 x 25/50/100 Y *	3	Matte	Inkjet; Electrostatic
Kraft Paper	50°F	48 x 50 Y*	3	Matte	Inkjet; Electrostatic
Polyester	50°F	36/48/54 x 10/50 Y*	3	Glossy	Inkjet; Electrostatic; Screen Print
Kraft Paper	60°F	49/54/60 x 50 Y*	3	Matte	Inkjet; Electrostatic
Polyester	60°F	48 x 50 Y*	3	High Gloss	Inkjet; Electrostatic; Screen Print
Kraft Paper	60°F	48 x 50 Y*	3	High Gloss	Inkjet; Electrostatic; Screen Print
None	170-245 F	38, 43, 51, 55, 61, 76	3	Gloss	
None	170-245 F	38, 43, 51, 55, 61, 76	3	Luster	
None	170-245 F	38, 43, 51, 76	3	Matte	
None	170-245 F	38, 43, 51, 55, 61, 76	3	Gloss	
None	170-245 F	38, 43, 51, 55	3	Gloss	
None	170-245 F	38, 43, 51, 55, 61	3	Luster	
None	170-245 F	38, 43, 51	3	Matte	
None	170-245 F	38, 43, 51	3	Textured	
None	170-245 F	38, 43, 51, 61	3	Gloss	
None	170-245 F	38, 43, 51	3	Gloss	
None	170-245 F	38, 43, 51	3	Matte	
None	170-245 F	38, 43, 51	3	Textured	
Polyethylene Coated Kraft With Grid	158-203 F	38, 43, 51	3	Textured	
None	210-240 F	25, 38, 43, 51	3	Gloss - Dry Erase	
None	170-245 F	38, 51, 61	3	Textured	
50# Bleached Glassine	PSA	38, 43, 51, 54, 55, 61	3	Gloss	
80# Paper PE and Silicone Coating	PSA	38, 43, 51, 54, 61	3	Gloss	
50# Bleached Glassine	PSA	38, 43, 51, 54, 55, 61	3	Luster	
80# Paper PE and Silicone Coating	PSA	38, 43, 51, 54, 61	3	Luster	
50# Bleached Glassine	PSA	38, 43, 51, 54, 55, 61	3	Matte	
80# Paper PE and Silicone Coating	PSA	38, 43, 51, 54, 61	3	Matte	
80# Paper PE and Silicone Coating	PSA	38, 43, 51, 54, 61	3	Textured Matte	
80# Paper PE and Silicone Coating	PSA	38, 43, 51, 54, 61	3	Textured Matte	
1.2 mil Polyester	PSA	38, 43, 51, 61	3	Textured, UL-410 Classified Slip resitant	
1.2 mil clear film	PSA	38, 43, 48, 51, 54	3	Textured, UL-410 Classified Slip resitant	
1.2 mil Polyester	PSA	38, 51, 54, 60	3	Gloss, With Removable Clear Premask	
1.2 mil Polyester	PSA	38, 51, 54, 60	3	Luster, With Removable Clear Premask	
1.2 mil Polyester	PSA	38, 51, 54, 60	3	Matte, DOES NOT HAVE REMOVABLE PREMASK	
1.5 mil Clear Polyester	PSA	38, 51	3	Textured Polycarbonate	
1.5 mil Clear Polyester	PSA	38, 51	3	Textured Polycarbonate	
1.5 mil Clear Polyester	PSA	31, 38, 51	3	Textured Polycarbonate	
50# White Glassine Liner	PSA	38, 43, 51, 54	3	Gloss (Dry Erase)	

2012 OVERLAMINATE

Product Name	Film Type	Color	Film Thickness (mil)	Film + Adhesive Thickeness (mil)	Adhesive Type
Arlon Graphics, LLC, 800-854-0361, www.MyPRINTResource.com/10003884					
Series 3200	Optically Clear Cast Overlaminate	Clear	2.0 mil	3.0 mil	Permanent
Series 3210	Cast Overlaminate	Clear	1.3 mil	2.3 mil	Permanent
Series 3220	Cast Overlaminate	Clear	2.0 mil	3.0 mil	Permanent
Series 3350	Anti-Graffiti PVDF	Clear	2.0 mil	3.1 mil	Permanent
Series 3420	Calendered Overlaminate	Clear	3.0 mil	4.0 mil	Permanent
Series 3520	Polyolefin Overlaminate	Clear	3.5 mil	4.6 mil	Permanent
Avery Dennison Graphics & Reflective Products Division, 800-282-8379, www.MyPRINTResource.com/10003974					
DOL 1060 Gloss Overlaminate	Cast	Clear	2.1	3.1	Yes
DOL 1080 Matte Overlaminate	Cast	Clear	2.1	3.1	Yes
DOL 1360 Gloss Overlaminate	Cast	Clear	1.3	2.3	
DOL 1370 Luster Overlaminate	Cast	Clear	1.3	2.3	
DOL 1380 Matte Overlaminate	Cast	Clear	1.3	2.3	
DOL 1460 Gloss Overlaminate	Cast	Clear	1.3	2.3	
DOL 1560 Optically Clear Overlaminate	Cast	Optically clear	2.1	3.1	
DOL 2060 Gloss Overlaminate	Calendered	Clear	3.1	4.1	Yes
DOL 2070 Luster Overlaminate	Calendered	Clear	3.1	4.1	Yes
DOL 2080 Matte Overlaminate	Calendered	Clear	3.1	4.1	Yes
DOL 3060 Gloss Promotional Overlaminate	Calendered	Clear	3.2	4.2	Yes
DOL 3070 Luster Promotional Overlaminate	Calendered	Clear	3.2	4.2	Yes
DOL 3080 Matte Promotional Overlaminate	Calendered	Clear	3.2	4.2	Yes
DOL 6060 Anti-Graffiti Overlaminate	Polyester	Clear	1	2	
Clear Focus Imaging, Inc., 800-307-7990, www.MyPRINTResource.com/10004440					
ClearLam	Optically clear Polyester	clear	1 mil	2 mils	Clear permanent acrylic
CurvaLam	Optically clear cast PVC	clear	2 mils	3 mils	Clear permanent acrylic
Coda Inc., 201-825-7400, www.MyPRINTResource.com/10004482					
Coda Canvas	Polyester-Vinyl	Clear	4 mil		PSA
Coda E-lam Erasable	Polypropylene	Clear	2 mil		PSA
Coda Glossy Paper	Polyester	Clear	2 mil		PSA
Coda Glossy Poly	Polyester	Clear	2 mil		PSA
Coda Lustre	Vinyl	Clear	4 mil		PSA
Coda Matte	Polyester	Clear	4 mil		PSA
D&K Group, Inc., 800-632-2314, www.MyPRINTResource.com/10004751					
FGM - SuperStick Heat Assist UV Vinyl	Vinyl	Matte		5	SuperStick
FGS - SuperStick Heat Assist UV Vinyl	Vinyl	Textured		5	SuperStick
FGV - SuperStick Heat Assist UV Vinyl	Vinyl	Textured		7	SuperStick
FGK - SuperStick Heat Assist UV Vinyl	Vinyl	Textured		7	SuperStick
FGC - Canvas Texture SuperStick Heat Assist UV Vinyl	Vinyl	Textured	8	10	SuperStick
FG - PSA Vinyl	Vinyl	Textured	5	6.25	Acrylic PSA
FGB - BrushStroke Texture SuperStick Heat Assist UV Vinyl	Vinyl	Textured	8	10	SuperStick
FS - PSA Vinyl	Vinyl	Textured	5	6.25	Acrylic PSA
GU - PSA Polyester	Polyester	Clear	2	3	Acrylic PSA
GUV - PSA Vinyl	Vinyl	Clear	3.5	4.5	Acrylic PSA
HCG - PSA UV Hardcoat	Polyester	Clear	1	2	Acrylic PSA
HCG - PSA UV Hardcoat	Polyester	Clear	3	5	Acrylic PSA
IG - Low-Temp UV Polyester	Polyester	Clear	1	3	Thermal Low Temp
IG - Low-Temp UV Polyester	Polyester	Clear	3	5	Thermal Low Temp
IG - Low-Temp UV Polyester	Polyester	Clear	2	5	Thermal Low Temp
IG - Low-Temp UV Polyester	Polyester	Clear	7	10	Thermal Low Temp
IG - Low-Temp UV Polyester	Polyester	Clear	4	10	Thermal Low Temp
IM - Diamond Hard Velvet Matte Low-Temp UV	Polyester	Matte	1	3	Thermal Low Temp
IM - Diamond Hard Velvet Matte Low-Temp UV	Polyester	Matte	3	5	Thermal Low Temp
IS - Low-Temp UV Polyester	Polyester	Luster	1	3	Thermal Low Temp
IS - Low-Temp UV Polyester	Polyester	Luster	3	5	Thermal Low Temp
LUB - PSA Vinyl	Vinyl	Luster	3	4	Acrylic PSA
MPU - PSA Diamond Hard Velvet Matte	Polyester	Matte	1		Acrylic PSA

RESOURCE CHART

Release Liner	Activation Temp (°F)	Width(s)	Core Size (inches)	Finish	Ink Compatibility
Polyester	N/A	30, 36, 54, 60	3	Gloss	N/A
Clay Coated	N/A	30, 48, 54, 60	3	Gloss	N/A
Clay Coated	N/A	30, 48, 54, 60	3	Gloss, luster, Satin, Matte	N/A
Clay Coated	N/A	49, 54	3	Satin	N/A
Clay Coated	N/A	30, 48, 54, 60	3	Gloss, Satin, Matte	N/A
Polyester	N/A	54	3	Gloss	N/A
Yes	Clear Permanent	3 mil transparent synthetic	N/A	24,30, 36, 48, 54, 60	3
	Clear Permanent	83 lb Kraft	N/A	24, 30, 36, 48, 54, 60	3
Yes	Clear Permanent	3 mil transparent synthetic	N/A	24, 30, 48, 54, 60	3
	Clear Permanent	83 lb Kraft	N/A	24, 48, 54 60	3
	Clear Permanent	83 lb Kraft	N/A	24, 48, 54, 60	3
Yes	Clear Permanent	3 mil transparent synthetic	N/A	24, 48, 54, 60	3
	Clear Permanent	1.5 mil Clear Polyester	N/A	48, 54	3
Yes	Clear Permanent	78 lb Bleach Kraft	N/A	24, 30, 38, 48, 51, 54, 60	3
Yes	Clear Permanent	78 lb Bleach Kraft	N/A	24, 30, 38, 44, 48, 51, 54, 60	3
Yes	Clear Permanent	78 lb Bleach Kraft	N/A	24, 30, 38, 48, 51, 54, 60	3
Yes	Clear Permanent	78 lb Bleach Kraft	N/A	24, 30, 54, 60	3
Yes	Clear Permanent	78 lb Bleach Kraft	N/A	24, 30, 54, 60	3
Yes	Clear Permanent	78 lb Bleach Kraft	N/A	24, 30, 54, 60	3
Yes	Clear Permanent	78 lb Bleach Kraft	N/A	48, 54, 60	3
2-mil Polyester	PSA	36,54	3 in.	Gloss	Solvent, Exo-Solvent, Mild Solvent, UV, Latex, Aqueous Inkjet, Screen Printing, Thermal Transfer
1.5-mil Polyester	PSA	36, 54, 60	3 in.	Gloss	Solvent, Exo-Solvent, Mild Solvent, UV, Latex, Aqueous Inkjet, Screen Printing, Thermal Transfer
Paper	Cold	All Types size up to 54	3	Canvas Texture	
Paper	Cold	All Types size up to 54	3	Semi-Gloss	
Paper	Cold	All Types size up to 54	3	Gloss	
Polyester	Cold	All Types size up to 54	3	High Gloss	
Paper	Cold	All Types size up to 54	3	Lustre	
Paper	Cold	All Types size up to 54	3	Flat	
None	160° - 200° F	25, 38, 41, 51, 61	3	Matte	Digital, Inkjet, & other heat-sensitive inks
None	160° - 200° F	25, 38, 41, 51	3	Sandtex	Digital, Inkjet, & other heat-sensitive inks
None	160° - 200° F	25, 38, 41, 51, 61	3	Velvet	Digital, Inkjet, & other heat-sensitive inks
None	160° - 200° F	25, 38, 41, 51, 61	3	Textured	Digital, Inkjet, & other heat-sensitive inks
None	160° - 200° F	25, 38, 41, 51, 61	3	Canvas	Digital, Inkjet, & other heat-sensitive inks
Film		25, 38, 51, 61	3	Textured	All Types
None	160° - 200° F	25, 38, 41, 51, 61	3	BrushStroke	Digital, Inkjet, & other heat-sensitive inks
Film	-	25, 38, 51	3	Sandtex	All Types
Film	-	25, 38, 41, 51, 54, 61	3	Gloss	All Types
Paper	-	25, 38, 41, 51, 54	3	Gloss	All Types
Film	-	38, 51	3	Gloss	All Types
Film	-	38, 51	3	Gloss	All Types
None	180° - 200° F	25, 38, 51, 55, 61	3	Gloss	Water-Based Inkjet
None	180° - 200° F	25, 38, 51, 55, 61	3	Gloss	Water-Based Inkjet
None	180° - 200° F	25, 38, 51, 55, 61	3	Gloss	Water-Based Inkjet
None	180° - 200° F	25, 33, 38, 43, 51, 55, 61	3	Gloss	Water-Based Inkjet
None	180° - 200° F	25, 33, 38, 43, 51, 55	3	Gloss	Water-Based Inkjet
None	180° - 200° F	25, 38, 51, 55, 61	3	Scuff Resistant Matte	Water-Based Inkjet
None	180° - 200° F	25, 38, 51, 55, 61	3	Scuff Resistant Matte	Water-Based Inkjet
None	180° - 200° F	25, 38, 51, 55, 61	3	Luster	Water-Based Inkjet
None	180° - 200° F	25, 38, 51, 55, 61	3	Luster	Water-Based Inkjet
Paper		25, 38, 41, 51, 54, 61	3	Luster	All Types
Film		25, 38, 41, 43, 51, 54, 61	3.00	Scuff Resistant Matte	All Types

2012 OVERLAMINATE

Product Name	Film Type	Color	Film Thickness (mil)	Film + Adhesive Thickeness (mil)	Adhesive Type
MPU2 - PSA Diamond Hard Velvet Matte	Polyester	Matte	2		Acrylic PSA
P0 - Thermal Polyester	Polyester	Clear	7	10	Thermal Copolymer
P0 - Thermal Polyester	Polyester	Clear	4	10	Thermal Copolymer
P3 - Thermal Polyester	Polyester	Clear	1	3	Thermal Copolymer
P5 - Thermal Polyester	Polyester	Clear	3	5	Thermal Copolymer
P5 - Thermal Polyester	Polyester	Clear	2	5	Thermal Copolymer
P7 - Thermal Polyester	Polyester	Clear	4	7	Thermal Copolymer
PH - PSA Polycarbonate	Polycarbonate	Clear	5	7	Acrylic PSA
PH - PSA Polycarbonate	Polycarbonate	Clear	10	12	Acrylic PSA
PH - PSA Polycarbonate	Polycarbonate	Clear	15	17	Acrylic PSA
PL - Thermal Polyester	Polyester	Luster	1	3	Thermal Copolymer
PNW3 - Diamond Hard Velvet Matte	Polyester	Matte	1	3	Thermal Copolymer
PNW5 - Diamond Hard Velvet Matte	Polyester	Matte	2	5	Thermal Copolymer
PNW10 - Diamond Hard Velvet Matte	Polyester	Matte	2	10	Thermal Copolymer
PS - Thermal Polyester	Polyester	Clear	0.5	1.7	Thermal Copolymer
PSG2 - SuperStick Heat Assist UV Polyester	Polyester	Gloss	2	3	SuperStick
PSG5 - SuperStick Heat Assist UV Polyester	Polyester	Gloss	3	5	SuperStick
PVCS - Solarguard	Calendared Vinyl	Clear	3	4	Solvent Acrylic PSA
SUB - PSA Vinyl	Vinyl	Clear	3	4	Acrylic PSA
Drytac Corp., 800-280-6013, www.MyPRINTResource.com/10005009					
ArtShield Canvastex UV 5.0 mil	HeatSet	Clear		5	Acrylic
ArtShield Deep Textured Canvastex UV 10.0 mil	HeatSet	Clear		10	Acrylic
ArtShield Emerytex UV 5.0 mil	HeatSet	Clear		5	Acrylic
ArtShield Gloss UV (Polyester) 2.6 mil	HeatSet	Clear		2.6	Acrylic
ArtShield Glossy UV (vinyl) 4.6 mil	HeatSet	Clear		4.6	Acrylic
ArtShield Linentex UV 5.0 mil	HeatSet	Clear		5	Acrylic
ArtShield Matte UV 4.0 mil	HeatSet	Clear		4	Acrylic
ArtShield Mattex UV 3.0 mil	HeatSet	Clear		3	Acrylic
ArtShield Satinex UV 3.0 mil	HeatSet	Clear		3	Acrylic
EnduraCoat Intego Gloss	Aqueous Liquid Coating	Clear			
EnduraCoat Intego Matte	Aqueous Liquid Coating	Clear			
EnduraCoat Photo Gloss	Aqueous Liquid Coating	Clear			
EnduraCoat Photo Lustre	Aqueous Liquid Coating	Clear			
EnduraCoat Photo Mattee	Aqueous Liquid Coating	Clear			
EnduraCoat Transit Gloss	Aqueous Liquid Coating	Clear			
EnduraCoat Transit Matte	Aqueous Liquid Coating	Clear			
EnduraCoat Ultra Mural	Aqueous Liquid Coating	Clear			
EnduraCoat Ultra Stain Resist	Aqueous Liquid Coating	Clear			
EnduraCoat UltraFlex Gloss	Aqueous Liquid Coating	Clear			
Instacure Digital Gloss	UV Curable Liquid Coating	Clear			
InstaCure Digital Matte	UV Curable Liquid Coating	Clear			
InstaCure Dry Erase	UV Curable Liquid Coating	Clear			
InstaCure Guardian Matte	UV Curable Liquid Coating	Clear			
InstaCure Guardian Satin	UV Curable Liquid Coating	Clear			
InstaCure Hard Coat Gloss	UV Curable Liquid Coating	Clear			
InstaCure Hard Coat Matte	UV Curable Liquid Coating	Clear			
InstaCure Low Melt Toner Gloss	UV Curable Liquid Coating	Clear			
InstaCure Photo Gloss	UV Curable Liquid Coating	Clear			
InstaCure Photo Matte	UV Curable Liquid Coating	Clear			
InstaCure POP	UV Curable Liquid Coating	Clear			
InstaCure Primer Coat Clear	UV Curable Liquid Coating	Clear			
InstaCure SuperFlex Gloss	UV Curable Liquid Coating	Clear			
InstaCure SuperFlex Satin-Matte	UV Curable Liquid Coating	Clear			
InstaCure UV White	UV Curable Liquid Coating	White			
InstaCure Variable Gloss	UV Curable Liquid Coating	Clear			
Interlam BioGloss 3 mil	PSA	Clear		3	Water-Based Acrylic
Interlam BioMatte 3 mil	PSA	Clear		3	Water-Based Acrylic
Interlam EcoGloss 2.5 mil	PSA	Clear		2.5	Water-Based Acrylic
Interlam EcoLustre 4.2 mil	PSA	Clear		4.2	Water-Based Acrylic
Interlam EcoTex 6.6 mil	PSA	Clear		6.6	Water-Based Acrylic
Interlam Emerytex UV 5.0 mil	PSA	Clear		5	Water-Based Acrylic
Interlam Glossy UV 3.0 mil	PSA	Clear		3	Water-Based Acrylic
Interlam Lustre UV 3.0 mil	PSA	Clear		3	Water-Based Acrylic

RESOURCE CHART

Release Liner	Activation Temp (°F)	Width(s)	Core Size (inches)	Finish	Ink Compatibility
Film		25, 38, 41, 43, 51, 54, 61	3.00	Scuff Resistant Matte	All Types
None	220° - 230° F	25, 33, 38, 43, 51, 55	3	Gloss	Solvent & Oil-based Inkjet
None	220° - 230° F	25, 33, 38, 43, 51, 55	3	Gloss	Solvent & Oil-based Inkjet
None	220° - 230° F	25, 33, 38, 43, 51, 55	3	Gloss	Solvent & Oil-based Inkjet
None	220° - 230° F	25, 33, 38, 43, 51, 55	3	Gloss	Solvent & Oil-based Inkjet
None	220° - 230° F	25, 33, 38, 43, 51, 55	3	Gloss	Solvent & Oil-based Inkjet
None	220° - 230° F	25, 33, 38, 43, 51, 55	3	Gloss	Solvent & Oil-based Inkjet
Film		31, 38, 51	3	Textured	All Types
Film		31, 38, 51	3	Textured	All Types
Film		31, 38, 51	3	Textured	All Types
None	220° - 230° F	25, 33, 38, 43, 51, 55	3	SemiGloss	Solvent & Oil-based Inkjet
None	220° - 230° F	25, 38, 51, 55	3	Scuff Resistant Matte	Solvent & Oil-based Inkjet
None	220° - 230° F	25, 38, 51, 55	3	Scuff Resistant Matte	Solvent & Oil-based Inkjet
None	220° - 230° F	25, 38, 51, 55	3	Scuff Resistant Matte	Solvent & Oil-based Inkjet
None	220° - 230° F	38, 43, 54, 55	3	Gloss	Solvent & Oil-based Inkjet
None	160° - 200° F	25, 38, 41, 51, 61	3	Gloss	Digital, Inkjet, & other heat-sensitive inks
None	160° - 200° F	25, 38, 41, 51, 61	3	Gloss	Digital, Inkjet, & other heat-sensitive inks
Paper	-	38, 51, 54	3	SemiGloss	All Types
Paper	-	25, 38, 41, 51, 54, 61	3	Matte	All Types
Yes	185 °F	25.5, 51	3	Embossed Canvas Texture Matte	All Types
Yes	185 °F	25.5, 51	3	Embossed ProNounced Canvas Texture	All Types
Yes	185 °F	25.5, 41, 51	3	Pebble Textured Matte	All Types
Yes	185 °F	25.5, 51	3	High-Gloss	All Types
Yes	185 °F	25.5, 51	3	Gloss	All Types
Yes	185 °F	25.5, 41, 51	3	Embossed Linen Texture Matte	All Types
Yes	185 °F	25.5, 41, 51	3	Dead Matte	All Types
Yes	185 °F	25.5, 41, 51	3	Satin-Matte	All Types
Yes	185 °F	25.5, 41, 51	3	Semi-Gloss	All Types
				Gloss	All Types
				Matte	All Types
				Gloss	All Types
				Lustre	All Types
				Matte	All Types
				Gloss, outdoor durable	All Types
				Matte, outdoor durable	All Types
				Matte, fade and mold resistant	All Types
				Gloss, anti-graffiti, outdoor durable	All Types
				Gloss, outdoor durable	All Types
				Gloss	All Types
				Matte	All Types
				Gloss, dry erase	All Types
				Matte, mold resistant, fire retardant	All Types
				Satin, mold resistant, fire retardant	All Types
				Gloss, scratch resistant	All Types
				Matte, scratch resistant	All Types
				Gloss	Low Melt Digital Toners
				Gloss	All Types
				Matte	All Types
				Gloss, anti-graffiti	All Types
				Gloss primer coat	All Types
				Gloss, flexible	All Types
				Satin-Matte, flexible	All Types
				Gloss white	All Types
				variable Satin to Gloss	All Types
Yes	N/A	25.5, 38, 51	3.00	Gloss, Biodegradable	All Types
Yes	N/A	24.5, 38, 49	3.00	Matte, Biodegradable	All Types
Yes	N/A	38, 41, 51, 55	3	Gloss	All Types
Yes	N/A	38, 41,51	3	Luster	All Types
Yes	N/A	38, 41, 51	3	Pebble Textured Satin	All Types
Yes	N/A	38, 41, 51	3	Pebble Textured Mattee	All Types
Yes	N/A	38, 51	3	Gloss	All Types
Yes	N/A	38, 41, 51	3	Luster	All Types

2012 OVERLAMINATE

Product Name	Film Type	Color	Film Thickness (mil)	Film + Adhesive Thickeness (mil)	Adhesive Type
Interlam Matte UV 4.0 mil	PSA	Clear		4	Water-Based Acrylic
Interlam Pro Deep Leather	PSA	Clear		8	Water-Based Acrylic
Interlam Pro Emerytex	PSA	Clear		5	Water-Based Acrylic
Interlam Pro Glossy	PSA	Clear		4	Water-Based Acrylic
Interlam Pro Lustre	PSA	Clear		4	Water-Based Acrylic
Interlam Pro Matte	PSA	Clear		4	Water-Based Acrylic
MediaShield Deep Textured Canvastex UV 10.0 mil	HeatSet	Clear		10	Solvent Acrylic
MediaShield Emerytex UV 5.0 mil	HeatSet	Clear		5	Solvent Acrylic
MediaShield Gloss UV 2.5 mil	HeatSet	Clear		2.5	Solvent Acrylic
MediaShield Matte UV 4.0 mil	HeatSet	Clear		4	Solvent Acrylic
MediaShield Mattex UV 3.0 mil	HeatSet	Clear		3	Solvent Acrylic
MediaShield Satinex UV 3.0 mil	HeatSet	Clear		3	Solvent Acrylic
MHL Brushed Silver	Thermal	Brushed Silver, opaque		1	
MHL EarthSmart Gloss 1 mil	Thermal	Clear		1	
MHL EarthSmart Matte 1 mil	Thermal	Clear		1	
MHL Frost UV 6.0 mil	Thermal	Clear		6	
MHL Gloss (Standard Temperature) 1.7 mil	Thermal	Clear		1.7	
MHL Gloss (Standard Temperature) 3.0 mil	Thermal	Clear		3	
MHL High Gloss Silver	Thermal	Silver, opaque		1	
MHL Impervo UV 10.0 mil	Thermal	Clear		10	
MHL Impervo UV 5.0 mil	Thermal	Clear		5	
MHL Lustre UV 3.0 mil	Thermal	Clear		3	
MHL Lustre UV 5.0 mil	Thermal	Clear		5	
MHL Matte UV 1.7 mil	Thermal	Clear		1.7	
MHL Matte UV 3.0 mil	Thermal	Clear		3	
MHL Quartz UV 5.0 mil	Thermal	Clear		5	
MHL Scribe UV 3.0 mil	Thermal	Clear		3	
MHL Velvet Touch 1.4 mil	Thermal	Clear		1.4	
MHLGloss UV 10.0 mil	Thermal	Clear		10	
MHLGloss UV 15.0 mil	Thermal	Clear		15	
MHLGloss UV 3.0 mil	Thermal	Clear		3	
MHLGloss UV 5.0 mil	Thermal	Clear		5	
MSR Matte Scuff Resistant	Thermal	Clear		1.5	
Protac Anti-grafitti UV 2.0 mil	PSA	Clear		2	Solvent Acrylic
Protac Antique Leather 4.0 mil	PSA	Clear		4	Solvent Acrylic
Protac CanvasTex 5.0 mil	PSA	Clear		5	Solvent Acrylic
Protac Emerytex 5.0 mil	PSA	Clear		5	Solvent Acrylic
Protac Hearts 3.0 mil	PSA	Clear		3	Solvent Acrylic
Protac Hessian 5.0 mil	PSA	Clear		5	Solvent Acrylic
Protac High Gloss 10.0 mil	PSA	Clear		10	Solvent Acrylic
Protac High Gloss 5.0 mil	PSA	Clear		5	Solvent Acrylic
Protac Ice 5.0 mil	PSA	Clear		5	Solvent Acrylic
Protac Linentex 5.0 mil	PSA	Clear		5	Solvent Acrylic
Protac Lustre 4.2 mil	PSA	Clear		4.2	Solvent Acrylic
Protac Matte 4.0 mil	PSA	Clear		4	Solvent Acrylic
Protac Polycarbonate 10.0 mil	PSA	Clear		10	Solvent Acrylic
Protac Polycarbonate 15.0 mil	PSA	Clear		15	Solvent Acrylic
Protac Polycarbonate 5.0 mil	PSA	Clear		5	Solvent Acrylic
Protac Scribe 2.5 mil	PSA	Clear		2.5	Solvent Acrylic
Protac SheenTex 4.2 mil	PSA	Clear		4.2	Solvent Acrylic
Protac Sparkle 3.0 mil	PSA	Clear		3	Solvent Acrylic
Protac Steel 4.0 mil	PSA	Clear		4	Solvent Acrylic
WeatherShield Emerytex 3mil	PSA	Clear		3	Solvent
WeatherShield Glossy 4 mil	PSA	Clear		4	Solvent
WeatherShield Lustre 4 mil	PSA	Clear		4	Solvent
WeatherShield Matte 4 mil	PSA	Clear		4	Solvent
WindowFX Permanent UV 2.0 mil	PSA	Clear		2	Solvent
WindowFX Removable UV 2.0 mil	PSA	Clear		2	Solvent
FLEXcon, 508-885-8440, www.MyPRINTResource.com/10005383					
BUSart OV5020L (bus posters)	Vinyl	Clear	3.5	4.4	Permanent
BUSart OV5040C (bus & train wraps)	Vinyl	Clear	3.5	4.4	Permanent

RESOURCE CHART

Release Liner	Activation Temp (˚F)	Width(s)	Core Size (inches)	Finish	Ink Compatibility
Yes	N/A	38, 41, 51	3	Matte	All Types
Yes	N/A	25, 51	3	Deep Leather Texture, 3+ years outdoor durable	All Types
Yes	N/A	38, 51, 61	3	Pebble Textured, 3+ years outdoor durable	All Types
Yes	N/A	38, 51, 61	3	Glossy, 3+ years outdoor durable	All Types
Yes	N/A	38, 51, 61	3	Lustre, 3+ years outdoor durable	All Types
Yes	N/A	38, 51, 61	3	Matte, 3+ years outdoor durable	All Types
Yes	185 °F	25.5, 51	3	Embossed ProNounced Canvas Texture	All Types
Yes	185 °F	38, 51, 55	3	Pebble Textured Matte	All Types
Yes	185 °F	38, 51	3	High-Gloss	All Types
Yes	185 °F	25.5, 38, 41, 51, 55	3	Dead Matte	All Types
Yes	185 °F	38, 41, 51, 55	3	Satin-Matte	All Types
Yes	185 °F	38, 41, 51, 55	3	Semi-Gloss	All Types
No	194 °-248 °F	51	3	Brushed Silver foil, printable	UV
No	230 °F	51	3	Gloss, Biodegradable	All Types
No	230 °F	51	3	Matte, Biodegradable	All Types
Yes	190 °F	38, 51, 61	3	Embossed, Crystal Texture(Luster)	All Types
Yes	190 °F	38, 51	3	High Gloss	All Types
Yes	190 °F	38, 51, 55	3	High Gloss	All Types
No	167 °-212 °F	51	3	Silver Foil, Printable	UV
Yes	190 °F	25, 38, 51	3	Lustre/Matte	All Types
Yes	190 °F	25, 38, 43, 51	3	Lustre/Matte	All Types
Yes	190 °F	25, 38, 43, 51, 55	3	Luster	All Types
Yes	190 °F	25, 38, 43, 51, 55, 61	3	Luster	All Types
Yes	190 °F	51, 61	3	Matte	All Types
Yes	190 °F	25, 38, 43, 51, 55, 61	3	Matte	All Types
Yes	190 °F	38, 51	3	Pebble Textured (Luster/Matte)	All Types
Yes	190 °F	25, 38, 43, 51	3	Dry-Erase Gloss	All Types
No	221 ° - 240°F	51	3	Velvet Matte	All Types
Yes	190 °F	25, 38, 43, 51, 55, 61	3	High Gloss	All Types
Yes	190 °F	38, 51	3	High Gloss	All Types
Yes	190 °F	25, 38, 43, 51, 55, 61	3	High Gloss	All Types
Yes	190 °F	25, 38, 43, 51, 55, 61	3	High Gloss	All Types
No	203 ° - 248 °F	51	3	Matte, Scuff Resistant	All Types
Yes	N/A	51	3	Satin, Anti Graffitti/Pollution Protection	All Types
Yes	N/A	25.5, 51	3	Embossed Leather Textured Semi-Matte	All Types
Yes	N/A	25.5, 51	3	Embossed Canvas Texture	All Types
Yes	N/A	25.5, 38, 41, 43, 51, 61	3	Pebble Textured Matt	All Types
Yes	N/A	25, 50	3	Digitized Heart Effect	All Types
Yes	N/A	25.5, 51	3	Heavy Canvas Textured Semi-Matte	All Types
Yes	N/A	54	3	Gloss	All Types
Yes	N/A	25.5, 38, 51	3	High Gloss	All Types
Yes	N/A	25.5, 51	3	Textured Semi-Matte	All Types
Yes	N/A	25.5, 51	3	Embossed Linen Texture	All Types
Yes	N/A	25.5, 38, 41, 43, 51, 61	3	Luster	All Types
Yes	N/A	25.5, 38, 41, 43, 51, 61	3	Dead Matte	All Types
Yes	N/A	38, 51, 60	3	Pebble-Textured Velvet Matte	All Types
Yes	N/A	38, 51, 60	3	Pebble-Textured Velvet Matte	All Types
Yes	N/A	38, 51, 60	3	Pebble-Textured Velvet Matte	All Types
Yes	N/A	25.5, 38, 41 51	3	Dry-Erase/Gloss	All Types
Yes	N/A	38, 41, 51, 61	3	Textured Satin/Luster	All Types
Yes	N/A	25, 50	3	Digitized Sparkle Effect	All Types
Yes	N/A	25.5, 51	3	Brushed Metal Semi-Matte	All Types
Yes	N/A		3	Pebble Textured	All Types
Yes	N/A		3	Glossy	All Types
Yes	N/A		3	Lustre	All Types
Yes	N/A		3	Matte	All Types
Yes	N/A	25.5, 38, 51	3	Clear, Printable	UV, Solvent
Yes	N/A	20.5, 41, 51	3	Clear, Printable	UV, Solvent
Paper	N/A	54, 62	3, 6	Luster	Solvent, UV
Paper	N/A	54	3, 6	Gloss	Solvent, UV

2012 OVERLAMINATE

Product Name	Film Type	Color	Film Thickness (mil)	Film + Adhesive Thickeness (mil)	Adhesive Type
BUSart OV5055 (window perf)	Vinyl	Optically Clear	2	3.1	Permanent
FLEXmark floor art OP6607	Polyolefin	Clear	3.6	4.7	Permanent
FLEXmark floor art OV6604 Clear Safari (Carpets)	Vinyl	Clear	23	25	Permanent
FLEXmark OV 6601 (Floors)	Vinyl	Clear	6.2	7.8	Permanent
FLEXmark OV 6602 (Floors)	Vinyl	Clear	4	5	Permanent
FLEXmark OV6603 (Floors)	Vinyl	Clear	6.2	7.9	Permanent
JETbond 43108	Vinyl	Clear	3.5	4.3	Permanent
JETbond 43138	Vinyl	Clear	3.5	4.3	Permanent
JETbond 43198UV	Vinyl	Clear	3.5	5	Permanent
JETbond 44138	Vinyl	Clear	3.5	4.4	Permanent
JETbond 44158	Vinyl	Clear	3.5	4.4	Permanent
GBC, 800-723-4000, www.MyPRINTResource.com/10005486					
Accushield	Liquid lamination alternative			0.3	High Temp
Arctic Anti-Graffiti	PCTFE		1 mil		PSAA
Arctic Laminates	PET, PVC, Polycarbonate and OPP PSA films			1, 2, 3, 5, 7, 8, 10	PSA
Nap-Lam I	PET			1.5, 3. 5	High Temp
Nap-Lam II	PET			1.5, 3, 5, 10	Standard
Octiva	PET and OPP (polypropylene) thermal films			1.5, 1.7, 3, 5, 10	Standard
Octiva Lay-Flat/Digital	Nylon			1.5	Standard and Digital
Octiva Light	PET (Polyester)			3, 5, 10	Standard
Octiva Lo-Melt	PET and PVC (vinyl) thermal films			3, 5, 10	Lo-Melt
Octiva Lo-Melt backing films	Opaque PET and Multi-layered PET			3, 5, 6, 10, 11	Lo-Melt
Octiva OPP/Digital	OPP			1.4, 1.5, 1.7	Standard and Digital
Octiva Polyester/Digital	PET			1.5, 3, 5	Standard and Digital
Hexis USA LLC, 888-AT-HEXIS, www.MyPRINTResource.com/10005836					
AG400M	Polyester anti-graffiti	Clear	0.9		Acrylic Solvent-Based
AG700	Polyester anti-graffiti	Clear	1.4		Acrylic Solvent-Based
AG800	Polyester anti-graffiti	Clear	3.9		Acrylic Solvent-Based
AGCR700	Polyester anti-graffiti, reinforced adhesive	Clear	1.4		Acrylic Solvent-Based
AM060	Anti-microbial vinyl	Clear	2.4		Acrylic Solvent-Based
AM060M	Anti-microbial vinyl	Clear	2.4		Acrylic Solvent-Based
AMGSOL200M	Anti-microbial for floors	Clear	7.9		Acrylic Solvent-Based
DWP002B	Erasable whiteboard	Clear	3.5		Acrylic Solvent-Based
GSOL170	PVC for floor graphics	Clear	6.7		Acrylic Solvent-Based
PC30G2	Cast vinyl with UV-protection	Clear	1.2		Acrylic Solvent-Based
PC30M2	Cast vinyl with UV-protection	Clear	1.2		Acrylic Solvent-Based
PC30M3	Cast vinyl with UV-protection	Clear	1.2		Acrylic Solvent-Based
PC50MICP2	Cast for micro-perofrated window films	Clear	2		Acrylic Solvent-Based
PG836	Polyester for micro-perofrated window films	Clear	1.4		Acrylic Solvent-Based
PL300CG2	Latex	Clear	1.2		Acrylic Solvent-Based
PSPOP	PVC for floor graphics	Clear	3.9		Acrylic Solvent-Based
TE25B	Tedlar long-term UV-protect	Clear			Acrylic Solvent-Based
V650B	Promotional vinyl	Clear	3		Acrylic Solvent-Based
V650M	Promotional vinyl	Clear	3		Acrylic Solvent-Based
V700B	Intermediate vinyl with UV-protection	Clear	3		Acrylic Solvent-Based
V700M	Intermediate vinyl with UV-protection	Clear	3		Acrylic Solvent-Based
V700S	Intermediate vinyl with UV-protection	Clear	3		Acrylic Solvent-Based
V750B	High performance vinyl with UV-protection	Clear	2.8		Acrylic Solvent-Based
V750M	High performance vinyl with UV-protection	Clear	2.8		Acrylic Solvent-Based
VCR750B	High performance vinyl, reinforced adhesive	Clear	2.8		Acrylic Solvent-Based

RESOURCE CHART

Release Liner	Activation Temp (°F)	Width(s)	Core Size (inches)	Finish	Ink Compatibility
Polyester	N/A	54	3, 6	Gloss	Solvent, UV
Polyester	N/A	60	3, 6	Gloss	UV
Paper	N/A	54	3, 6	Safari textured	Solvent, UV
Paper	N/A	54	3, 6	Velvet	Solvent, UV
Polyester	N/A	54	3, 6	Gloss	Solvent, UV
Paper	N/A	54	3, 6	Safari Textured	Solvent, UV
Paper	N/A	54, 60	3, 6	Matte	Solvent, UV
Paper	N/A	54, 60	3, 6	Matte	Solvent, UV
Paper	N/A	54, 60	3, 6	Matte	Solvent, UV
Paper	N/A	54, 60	3, 6	Luster	Solvent, UV
Paper	N/A	54, 60	3, 6	Luster	Solvent, UV
y	275-285	25, 38, 55, 61	3, 2.25	Clear, Matte	
Y	0-110	54	3	Gloss	
Y	0-110	25, 38, 43, 51, 55, 61, 79	3, 2.25	Gloss, Lustre, Matte, Textured Satin, Polycarb, Light Barrier, FloorMat, Graffiti, Write Erase, UV Cast Sand/Gloss, Choice, Select	
N	250-270	9, 12, 18, 25	1, 2.25	Clear	
N	210-250	Varying from 4 to 38	1, 2.25, 3	Clear, Matte	
N	210-250	25, 38, 43, 51, 55, 61	3	Gloss, Lustre, Matte scuff free Matte, hard coat, write erase	
N	Standard = 220-260 Digital = 240-270	Varying from 10.75 to 19.5	2.25, 3	Clear, Matte	
N	210-250	38, 43, 51, 55, 61	3	Gloss, Matte	
Some	185-210	38, 43, 51, 55	3	Gloss, Lustre, Matte, Hard Coat Matte/ Lustre, Textured Satin, Emboss 50, Canvas, Heat Set Gloss/Lustre	
N	185-210	38, 43, 51	3	Light Barrier, White	
N	Standard = 220-260 Digital = 240-270	Varying from 10.75 to 19.5	3	Clear, Scuff Free Matte	
N	Standard = 220-260 Digital = 240-270	Varying from 10.75 to 19.5	1, 2.25, 3	Clear, Matte	
Silicone Paper	Cold Laminate	54	3	Matte	
Silicone Paper	Cold Laminate	51.6 54 60	3	Gloss	
Polyester	Cold Laminate	60	3	Gloss	
Silicone Paper	Cold Laminate	54	3	Gloss	
Silicone Paper	Cold Laminate	54 60	3	Gloss	
Silicone Paper	Cold Laminate	54 60	3	Matte	
Silicone Paper	Cold Laminate	60	3	Matte	
PE-Coated	Cold Laminate	48 54	3	Gloss	
Silicone Paper	Cold Laminate	51.6	3	Grained	
PE-Coated	Cold Laminate	54 60	3	Gloss	
PE-Coated	Cold Laminate	54 60	3	Matte	
PE-Coated	Cold Laminate	54	3	Matte	
Polyester	Cold Laminate	54 60	3	Gloss	
Polyester	Cold Laminate	54 60	3	Gloss	
Kraft Paper	Cold Laminate	54	3	Gloss	
Silicone Paper	Cold Laminate	36 42	3	Satin	
Silicone Paper	Cold Laminate	60	3	Gloss	
Silicone Paper	Cold Laminate	41 54 63	3	Gloss	
Silicone Paper	Cold Laminate	41 54 63	3	Matte	
Silicone Paper	Cold Laminate	37.4 41 51.6 54 63	3	Gloss	
Silicone Paper	Cold Laminate	37.4 41 51.6 54 63	3	Matte	
Silicone Paper	Cold Laminate	37.4 41 51.6 54 63	3	Satin	
Silicone Paper	Cold Laminate	41 59 63	3	Gloss	
Silicone Paper	Cold Laminate	54 63	3	matt	
Silicone Paper	Cold Laminate	54 63	3	Gloss	

2012 OVERLAMINATE

Product Name	Film Type	Color	Film Thickness (mil)	Film + Adhesive Thickeness (mil)	Adhesive Type
IJ TechNologies, 800-356-6962, www.MyPRINTResource.com/10005923					
Black Diamond Eclipse	Liquid	Clear			
Black Diamond Eclipse	Liquid	Clear			
Black Diamond Eclipse	Liquid	Clear			
LexJet Corp., 800-453-9538, www.MyPRINTResource.com/10006398					
LexJet 1.7 Mil Gloss Thermal	Polyester	Clear	0.7	1	Ethylene-Vinyl Acetate
LexJet 1.7 Mil Matte Thermal	Polyester	Clear	0.7	1	Ethylene-Vinyl Acetate
LexJet 10 Mil ArmorGuard Ultra Low Gloss UV	Polyester	Clear	7	3	Ethylene-Vinyl Acetate
LexJet 10 Mil DisplayGuard Ti UV Low Melt	Polyester	Clear	7	3	Ethylene-Vinyl Acetate
LexJet 10 Mil Gloss UV Premium Low Melt	Polyester	Clear	7	3	Ethylene-Vinyl Acetate
LexJet 10 Mil Gloss UV Standard Low Melt	Polyester	Clear	4	6	Ethylene-Vinyl Acetate
LexJet 3 Mil Gloss UV Premium Low Melt	Polyester	Clear	1	2	Ethylene-Vinyl Acetate
LexJet 3 Mil Luster UV Standard Low Melt	Polyester	Clear	0.5	2.5	Ethylene-Vinyl Acetate
LexJet 3 Mil Matte UV Standard Low Melt	Polyester	Clear	0.5	2.5	Ethylene-Vinyl Acetate
LexJet 5 Mil ArmorGuard Ultra Low Gloss	Polyester	Clear	3	2	Ethylene-Vinyl Acetate
LexJet 5 Mil DisplayGuard Ti UV Low Melt	Polyester	Clear	3	2	Ethylene-Vinyl Acetate
LexJet 5 Mil Gloss UV Premium Low Melt	Polyester	Clear	3	2	Ethylene-Vinyl Acetate
LexJet 5 Mil Gloss UV Standard Low Melt	Polyester	Clear	2	3	Ethylene-Vinyl Acetate
LexJet 5 Mil Luster UV Standard Low Melt	Polyester	Clear	2	3	Ethylene-Vinyl Acetate
LexJet 7 Mil Textured UV Low Melt	Polyester	Clear	5	2	Ethylene-Vinyl Acetate
LexJet Dry Erasable Gloss Laminate (2 Mil)	Polypropylene	Clear	2	1	Optically Clear Permanent Acrylic
LexJet Elite Luster UV Vinyl Laminate (3.2 Mil)	Vinyl	Clear	3.2	1	Optically Clear Solvent Acrylic, Permanent
LexJet Elite Matte UV Vinyl Laminate (3.2 Mil)	Vinyl	Clear	3.2	1	Optically Clear Solvent Acrylic, Permanent
LexJet Elite Polycarbonate Laminate (10 Mil)	Polycarbonate	Clear	10	2	Optically Clear Solvent Acrylic, Permanent
LexJet Elite Polycarbonate Laminate (15 Mil)	Polycarbonate	Clear	15	2	Optically Clear Solvent Acrylic, Permanent
LexJet Elite Polycarbonate Laminate (5 Mil)	Polycarbonate	Clear	5	2	Optically Clear Solvent Acrylic, Permanent
LexJet Elite Textured Coex Laminate (10 Mil)	Rigid co-polymer	Clear	10	2	Optically Clear Solvent Acrylic, Permanent
LexJet Elite Textured Coex Laminate (15 Mil)	Rigid co-polymer	Clear	15	2	Optically Clear Solvent Acrylic, Permanent
LexJet Elite Textured Coex Laminate (5 Mil)	Rigid co-polymer	Clear	5	2	Optically Clear Solvent Acrylic, Permanent
LexJet Floor Gloss Laminate (3 Mil)	Vinyl	Clear	3	1	Optically Clear Permanent Acrylic
LexJet Floor Velvet Laminate (5 Mil)	Vinyl	Clear	5	1	Optically Clear Permanent Acrylic
LexJet Gloss Polyester Laminate (2 Mil)	Polyester	Clear	2	1	Optically Clear Permanent Acrylic
LexJet Optically Clear Cast Gloss Laminate	Cast Vinyl	Clear	2	1	Optically Clear Permanent Acrylic
LexJet Performance Gloss Vinyl Laminate (3 Mil)	Vinyl	Clear	3	1	Optically Clear Permanent Acrylic
LexJet Performance Matte Vinyl Laminate (3 Mil)	Vinyl	Clear	3	1	Optically Clear Permanent Acrylic
LexJet Performance Satin UV Vinyl Laminate (3 Mil)	Vinyl	Clear	3	1	Optically Clear Solvent Acrylic, Permanent
LexJet Performance Textured Polypropylene Laminate (10 Mil)	Polypropylene	Clear	10	1.25	Optically Clear Solvent Acrylic, Permanent
LexJet Performance Textured Polypropylene Laminate (5 Mil)	Polypropylene	Clear	5	1.25	Optically Clear Solvent Acrylic, Permanent
LexJet Simple Flo Wrap Gloss UV Laminate (2.4 Mil)	Vinyl	Clear	2.4	1	Optically Clear Permanent Acrylic
MACtac, 866-622-8223, www.MyPRINTResource.com/10006495					
ColorGard 8200 Series	Vinyl	Clear	3.2	4.2	Clear Permanent
ColorGard 8300 Series	Vinyl	Clear	3.2	4.2	Clear Permanent
ColorGard™ 8000 Series	Vinyl	Clear	3	4	Clear Permanent
PERMACOLOR Enhancers	Vinyl	Clear	1.5	2.5	Clear Permanent
PERMACOLOR Enhancers	Vinyl	Clear	1.5	2.5	Clear Permanent
PERMACOLOR Enhancers	Vinyl	Clear	1.5	2.5	Clear Permanent
PERMACOLOR LF6550	Vinyl	Clear	2.9	3.9	Clear Permanent
PERMACOLOR LF6560	Vinyl	Clear	2.9	3.9	Clear Permanent
PERMACOLOR RAYZor	Vinyl	Clear	1.5	2.5	Clear Permanent
Permacolor RAYZor	Vinyl	Clear	1.5	2.5	Clear Permanent
PERMACOLOR RAYZor	Vinyl	Clear	1.5	2.5	Clear Permanent
PERMACOLOR ThermaFlex TL5350	Polyester	Clear	7	3	Clear Permanent
PERMACOLOR ThermaFlex TL5450	Polyester	Clear	3	2	Clear Permanent
PERMACOLOR Thermal TL2030	Polyester	Clear	1	2	Clear Permanent
PERMACOLOR Thermal TL2050	Polyester	Clear	3	2	Clear Permanent
PERMACOLOR Thermal TL2100	Polyester	Clear	7	3	Clear Permanent
PERMACOLOR Thermal TL4030	Polyester	Clear	1	2	Clear Permanent
PERMACOLOR Thermal TL5050	Polyester	Clear	3	2	Clear Permanent
PERMACOLOR Thermal TL5150	Polyester	Clear	7	3	Clear Permanent
PERMACOLOR Thermal TL5630	Polyester	Clear	1	2	Clear Permanent
PERMACOLOR Thermal TL6150	Vinyl	Clear	7	3	Clear Permanent

RESOURCE CHART

Release Liner	Activation Temp (˚F)	Width(s)	Core Size (inches)	Finish	Ink Compatibility
				Gloss	Pigment
				Satin	Pigment
				Matte	Pigment
N/A	220°-230°F	25, 38, 40, 51, 55	2.25, 3	Gloss	All Types
N/A	220°-230°F	38	3	Matte	All Types
N/A	170°F (78°C)	38, 43, 51	3	Matte	All Types
N/A	170°F (78°C)	25, 38, 43, 51	3	Textured	All Types
N/A	170°F (78°C)	25, 38, 43, 51	3	Gloss	All Types
N/A	170°F (78°C)	25, 38, 43, 51	3	Gloss	All Types
N/A	170°F (78°C)	25, 38, 43, 51, 60, 61	3	Gloss	All Types
N/A	170°F (78°C)	25, 38, 43, 51, 55, 61	3	Luster	All Types
N/A	170°F (78°C)	38, 43, 51	3	Matte	All Types
N/A	170°F (78°C)	25, 38, 43, 51	3	Matte	All Types
N/A	170°F (78°C)	25, 38, 43, 51	3	Textured	All Types
N/A	170°F (78°C)	38, 51	3	Gloss	All Types
N/A	170°F (78°C)	25, 38, 43, 51, 55	3	Gloss	All Types
N/A	170°F (78°C)	38, 43, 51	3	Luster	All Types
N/A	160°F-200°F	38, 41, 51, 61	3	Textured	All Types
4 Mil, 53# Polycoated Kraft Paper	No heat needed	38, 54	3	Gloss	All Types
2.5 Mil, 40# Polycoated Kraft Paper	No heat needed	38, 43, 51, 61	3	Luster	All Types
2.5 Mil, 40# Polycoated Kraft Paper	No heat needed	38, 51	3	Matte	All Types
1.5 Mil Clear Polyseter	No heat needed	38, 51	3	Textured	All Types
1.5 Mil Clear Polyseter	No heat needed	30, 38, 51	3	Textured	All Types
1.5 Mil Clear Polyseter	No heat needed	38, 51	3	Textured	All Types
1.5 Mil Clear Polyseter	No heat needed	38, 51	3	Textured	All Types
1.5 Mil Clear Polyseter	No heat needed	38, 51, 61	3	Textured	All Types
1.5 Mil Clear Polyseter	No heat needed	38, 51	3	Textured	All Types
4 Mil, 53# Polycoated Kraft Paper	No heat needed	54	3	Gloss	All Types
4 Mil, 53# Polycoated Kraft Paper	No heat needed	54	3	Textured	All Types
1.5 Mil Clear Polyseter	No heat needed	38, 51, 61	3	Gloss	All Types
1.2 Mil Clear Polyester	No heat needed	54	3	Gloss	All Types
4 Mil, 53# Polycoated Kraft Paper	No heat needed	38, 54	3	Gloss	All Types
4 Mil, 53# Polycoated Kraft Paper	No heat needed	38, 54, 61	3	Matte	All Types
2.5 Mil, 40# Polycoated Kraft Paper	No heat needed	38, 43, 51, 54, 61	3	Satin	All Types
2.5 Mil, 40# Polycoated Kraft Paper	No heat needed	38, 51	3	Textured	All Types
2.5 Mil, 40# Polycoated Kraft Paper	No heat needed	38, 51, 54	3	Textured	All Types
4 Mil, 53# Polycoated Kraft Paper	No heat needed	54, 60	3	Gloss	All Types
50# White	N/A	38, 51, 54, 60	3	Matte	Solvent, Latex, UV
50# White	N/A	38, 51, 54, 60	3	Lustre	Solvent, Latex, UV
50# White	N/A	38, 51, 54, 60	3	Gloss	Solvent, Latex, UV
80# White	N/A	54, 60	3	Silver Metallic	Solvent, Latex, UV
80# White	N/A	54, 60	3	Brilliant Crystal	Solvent, Latex, UV
80# White	N/A	54, 60	3	Prism Metallic	Solvent, Latex, UV
75# White	N/A	79	3	Matte	Solvent, Latex, UV
75# White	N/A	79	3	Gloss	Solvent, Latex, UV
50# White	N/A	54	3	Gloss	Solvent, Latex, UV
50# White	N/A	54, 60	3	Matte	Solvent, Latex, UV
Polyester	N/A	54	3	Gloss	Solvent, Latex, UV
NA	210°F/99°C	33, 38, 43, 51	3	Hard Coated Textured	Inkjet, Electrostatic, Digital, Laser
NA	200°F/94°C	38, 51	3	Hard Coated Textured	Inkjet, Electrostatic, Digital, Laser
NA	190°F/88°C	33, 38, 43, 51	3	Gloss	Inkjet, Electrostatic, Digital, Laser
NA	200°F/94°C	33, 38, 43, 51	3	Gloss	Inkjet, Electrostatic, Digital, Laser
NA	210°F/99°C	33, 38, 43, 51	3	Gloss	Inkjet, Electrostatic, Digital, Laser
NA	190°F/88°C	33, 38, 43, 51	3	Satin	Inkjet, Electrostatic, Digital, Laser
NA	200°F/94°C	33, 38, 43, 51	3	Hard Coated Matte	Inkjet, Electrostatic, Digital, Laser
NA	210°F/99°C	33, 38, 43, 51	3	Hard Coated Matte	Inkjet, Electrostatic, Digital, Laser
NA	190°F/88°C	33, 38, 43, 51	3	Satin	Inkjet, Electrostatic, Digital, Laser
NA	210°F/99°C	38, 51	3	Textured	Inkjet, Electrostatic, Digital, Laser

2012 OVERLAMINATE

Product Name	Film Type	Color	Film Thickness (mil)	Film + Adhesive Thickeness (mil)	Adhesive Type
PERMACOLOR Verde VL1200	Modified Polypropylene	Clear	3.1	4.1	Clear Permanent
PERMACOLOR Verde VL1300	Modified Polypropylene	Clear	3.1	4.1	Clear Permanent
PERMACOLOR Verde VL1000	Modified Polypropylene	Clear	3.1	4.1	Clear Permanent
PermaFlex IP6100 Series	Polycarbonate	Clear	10	11	Clear Permanent
PermaFlex IP6200 Series	Polycarbonate	Clear	5	6	Clear Permanent
PermaFlex PF6300	Vinyl	Clear	5	6	Clear Permanent
PermaFlex PF6400	Polyolefin	Clear	3.8	4.8	Clear Permanent
PermaFlex PF6500	Vinyl	Clear	4.3	5.3	Clear Permanent
PermaFlex IP6000 Series	Polycarbonate	Clear	15	16	Clear Permanent
PermaGard IP7200 Series	Vinyl	Clear	3.3	4.3	Clear Permanent
PermaGard IP7200 Series	Vinyl	Clear	3.5	4.5	Clear Permanent
PermaGard PG6000Series	Polypropylene Dry Erase	Clear	1.2	2.2	Clear Permanent
PermaGard PG7034Series	Polypropylene Dry Erase	Clear	1.2	2.2	Clear Permanent
PermaGard PG7285Series	Vinyl	Clear	2.8	3.8	Clear Permanent
PermaGard IP7000 Series	Polyester	Clear	2	3	Clear Permanent
PG7000 Series	Vinyl	Clear	3	4	Clear Permanent
PG7200 Series	Vinyl	Clear	3	4	Clear Permanent
PG7300 Series	Vinyl	Clear	3	4	Clear Permanent
Neschen-Americas, 410-540-8900, www.MyPRINTResource.com/10006859					
Neschen AccuCure Elite UV Fleet Gloss	N/A	Clear	Variable		
Neschen AccuCure Elite UV Fleet Luster	N/A	Clear	Variable		
Neschen AccuCure Elite UV Gloss	N/A	Clear	Variable		
Neschen AccuCure Elite UV Satin Matte	N/A	Clear	Variable		
SEAL Floor Guard	Vinyl	Clear	4	4/1	Solvent Acryllic
SEAL Jet Guard Crystal Matte	Polyester	Clear	3.4	3.4/2.6	Extruded Copolymer
SEAL Jet Guard Deep Crystal	Polyester	Clear	3.4	3.4/2.6	Extruded Copolymer
SEAL Jet Guard UV Gloss	Polyester	Clear	1,3,7,	1/2, 3/2, 7/3	Extruded Copolymer
SEAL Jet Guard UV Luster	Polyester	Clear	1	1/2	Extruded Copolymer
SEAL Jet Guard UV Matte	Polyester	Clear	1	1/2	Extruded Copolymer
SEAL Print Guard UV Gloss	Polyester	Clear	1	1/1	Solvent Acryllic
SEAL Print Guard UV Luster	Vinyl	Clear	2	2/1	Solvent Acryllic
SEAL Print Guard UV Satin Matte	Vinyl	Clear	2	2/1	Solvent Acryllic
SEAL Print Guard UV Ultra Matte	Vinyl	Clear	3	3/1	Solvent Acryllic
SEAL Print Shield Anti-Graffiti	PCTFE	Clear	1		Water-Based Acryllic
SEAL Print Shield Base Gloss	Vinyl	Clear	3	3/1	Water-Based Acryllic
SEAL Print Shield Base Luster	Vinyl	Clear	3	3/1	Water-Based Acryllic
SEAL Print Shield Base Matte	Vinyl	Clear	3	3/1	Water-Based Acryllic
SEAL Print Shield Base Textured Matte	Vinyl	Clear	3	3/1	Water-Based Acryllic
SEAL Print Shield Deep Crystal	Polyester	Clear	3.4	3.4/2.6	Water-Based Acryllic
SEAL Print Shield Floor Guard	Textured Vinyl	Clear	5		Water-Based Acryllic
SEAL Print Shield Polycarbonate	Polycarbonate	Clear	5, 10		Solvent Acryllic
SEAL Print Shield Standard UV Gloss	Vinyl	Clear	2.5	2.5/1	Water-Based Acryllic
SEAL Print Shield Standard UV Luster	Vinyl	Clear	2.5	2.5/1	Water-Based Acryllic
SEAL Print Shield Standard UV Matte	Vinyl	Clear	2.9	2.9/1.1	Water-Based Acryllic
SEAL ThermaShield Gloss	Polyester	Clear	0.5, 1, 2, 4	0.5/1.2, 1/2, 2/3, 4/6	Extruded Copolymer
SEAL ThermaShield Luster	Polyester	Clear	1	1/2	Extruded Copolymer
SEAL ThermaShield Matte	Polyester	Clear	1	1/2	Extruded Copolymer
SEAL Write	Polypropylene	Clear	1	1/1	Water-Based Acryllic
Oracal USA, 888-672-2251, www.MyPRINTResource.com/10007024					
ORAGUARD 200 Calendered EcoNomy PVC	Laminating film	Clear	2.5	N/A	Clear; Water-Based; Permanent
ORAGUARD 210 Intermediate Calendered PVC	Laminating film	Clear	2.5	N/A	Clear; Solvent-Based; Permanent
ORAGUARD 215 Intermediate Calendered PVC	Laminating film	Clear	2.75	N/A	Clear; Solvent-Based; Permanent
ORAGUARD 240 Anti-Graffiti	Laminating film	Clear	1	N/A	Clear; Solvent-Based; Permanent
ORAGUARD 250AS Skid-Resistant Calendered PVC	Laminating film	Clear	4.75	N/A	Clear; Solvent-Based; Permanent
ORAGUARD Series 255AS High Load Skid-Resistant Calendered PVC	Laminating film	Clear	6.5	N/A	Clear; Solvent-Based; Permanent
ORAGUARD Series 270 Stone Guard Paint Protection	Laminating film	Clear	6	N/A	Clear; Solvent-Based; Permanent
Quality Media & Laminating Solutions, 800-552-9427, www.MyPRINTResource.com/10007562					
Digiguard UV Gloss 10m	Polyester	Clear	4	6	Thermal
Digiguard UV Gloss 15m	Polyester	Clear	7	8	Thermal

RESOURCE CHART

Release Liner	Activation Temp (°F)	Width(s)	Core Size (inches)	Finish	Ink Compatibility
60# White	N/A	54	3	Matte	Solvent, Latex, UV
60# White	N/A	54	3	Luster	Solvent, Latex, UV
60# White	N/A	54	3	Gloss	Solvent, Latex, UV
Polyester	N/A	37, 51	6	Textured	Photo, Solvent, Latex, UV
Polyester	N/A	21, 31, 37, 51	3	Textured	Photo, Solvent, Latex, UV
Glassine	N/A	41, 54	3	Textured	Solvent, Latex, UV
50# White	N/A	54	3	Textured	Solvent, Latex, UV
50# White	N/A	38, 51	3	Textured	Solvent, Latex, UV
Polyester	N/A	37, 51	6	Textured	Photo, Solvent, Latex, UV
80# White	N/A	31, 37, 51, 61	3	Matte	Photo, Solvent, Latex, UV
80# White	N/A	31, 37, 51, 61	3	Lustre	Photo, Solvent, Latex, UV
Polyester	N/A	54	3	Gloss	Photo, Solvent, Latex, UV
Polyester	N/A	37, 41, 51, 60	3	Gloss	Photo, Solvent, Latex, UV
50# Kraft	N/A	79	3	Matte	Solvent, Latex, UV
Polyester	N/A	31, 37, 51, 61	3	Gloss	Photo, Solvent, Latex, UV
40# White	N/A	38, 51, 54, 60	3	Gloss	Solvent, Latex, UV
40# White	N/A	38, 51, 54, 60	3	Matte	Solvent, Latex, UV
40# White	N/A	38, 51, 54, 60	3	Lustre	Solvent, Latex, UV
				Gloss	
				Luster	
				Gloss	
				Satin Matte	
PE Coated Kraft Paper	195-215	38, 51	3	Textured	
N/A	185-205	38, 51	3	Matte	
N/A	185-205	38, 51	3	Matte	
N/A	185-205	25, 38, 43, 51, 55, 61	3	Gloss	
N/A	185-205	38, 43, 51	3	Luster	
N/A	185-205	25, 38, 51	3	Matte	
PE Coated Kraft Paper	185-195	38, 41, 51	3	Gloss	
PE Coated Kraft Paper	185-195	25, 38, 41, 51	3	Luster	
PE Coated Kraft Paper	185-195	25, 38, 41, 43, 51	3	Matte	
PE Coated Kraft Paper	185-195	41, 49	3	Matte	
Siliconized Clay Coated Paper	N/A	54	3	Gloss	
Siliconized Kraft Paper	N/A	38, 51, 54, 60	3	Gloss	
Siliconized Kraft Paper	N/A	38, 51, 54, 60	3	Luster	
Siliconized Kraft Paper	N/A	38, 51, 54, 60	3	Matte	
Siliconized Kraft Paper	N/A	38, 51, 54	3	Matte	
Siliconized Glassine	N/A	38	3	Satin	
Clay Coated	N/A	38, 51, 54, 60	3	Textured	
Polyester	N/A	38, 51	3	Luster	
Siliconized Glassine	N/A	38, 41, 51, 54, 61	3	Gloss	
Siliconized Glassine	N/A	25, 38, 41, 43, 51, 54, 61, 79	3	Luster	
Siliconized Glassine	N/A	38, 41, 51, 54, 61, 79	3	Matte	
N/A	185-235	38, 43, 51	3	Gloss	
N/A	185-235	38, 51	3	Luster	
N/A	185-235	38, 43, 51	3	Matte	
Siliconized Glassine	N/A	38, 51	3	Gloss	
Silicone-Coated Paper 55#	Cold	30; 36; 40; 50; 54' 60	3 or 6	Gloss; Semi-Gloss; Matte	N/A
Silicone-Coated Paper 55#	Cold	30; 36; 40; 50; 54' 60	3 or 6	Gloss; Semi-Gloss; Matte	N/A
Silicone-Coated Paper 55#	Cold	30; 36; 40; 50; 54' 60	3 or 6	Gloss; Semi-Gloss; Matte	N/A
Silicone-Coated Paper 55#	Cold	30; 36; 40; 50; 54' 60	3 or 6	High Gloss	N/A
Silicone-Coated Paper 55#	Cold	36; 40; 50; 54	3 or 6	Raised Non-Skid Textured	N/A
Silicone-Coated Paper 53#	Cold	36; 40; 50; 54	3 or 6	Raised Non-Skid Textured	N/A
Silicone-Coated Paper 84#	Cold	50	5 or 6	Gloss	N/A
	210-220	25 to 76	3	Gloss	All Types
	210-230	25 to 51	3	Gloss	All Types

2012 OVERLAMINATE

Product Name	Film Type	Color	Film Thickness (mil)	Film + Adhesive Thickeness (mil)	Adhesive Type
Digiguard UV Gloss 3m	Polyester	Clear	1	2	Thermal
Digiguard UV Gloss 5m	Polyester	Clear	2	3	Thermal
Digiguard UV Matte 3m	Polyester	Clear	1	2	Thermal
Digiguard UV Satin 3m	Polyester	Clear	1	2	Thermal
Digiguard UV Satin 5m	Polyester	Clear	2	3	Thermal
Digiguard Velvet Matte 3m	Polyester	Clear	1	2	Thermal
Digiguard Velvet Matte 5m	Polyester	Clear	2	3	Thermal
Duraguard UV Gloss	Polyester	Clear	2.5	1	Thermal
Duraguard UV Lustre	Vinyl	Clear	2.5	1	Thermal
Duraguard UV Matte	Vinyl	Clear	2.5	1	Thermal
Duraguard UV Ultra Matte	Vinyl	Clear	2.5	1	Thermal
Duraguard UV Velvet	Vinyl	Clear	5	1	Thermal
Exhibitshield UV	Copolymer film	Clear	5, 10 & 15	1.2	Solvent Acrylic
FloorTalkers EcoNomy Floorgraphic	Polypropylene	Clear	3.7	1.2	Acrylic
Gallery Guard	Cast polymer	Clear	2	1.2	Solvent Acrylic
Hardguard Clear Texture 10m	Polyester	Clear	7	3	Thermal
Hardguard Clear Texture 5m	Polyester	Clear	3	2	Thermal
Hardguard Diamond	Polypro/ Polyester	Clear	3.5	2.5	Thermal
Hardguard Dry Erase	Polypropylene	Clear	2	1	Thermal
Hardguard Gloss 1.7	Polyester	Clear	1.2	0.5	Thermal
Hardguard Gloss 10m	Polyester	Clear	7	3	Thermal
Hardguard Gloss 3m	Polyester	Clear	2	1	Thermal
Hardguard Gloss 5m	Polyester	Clear	3	2	Thermal
Hardguard Matte 3m	Polyester	Clear	2	1	Thermal
Hardguard Satin 3m	Polyester	Clear	2	1	Thermal
Hardguard UV Lustre 10m	Polyester	Clear	7	3	Thermal
Hardguard UV Lustre 5m	Polyester	Clear	3	2	Thermal
Hardguard UV Matte 10m	Polyester	Clear	7	3	Thermal
Hardguard UV Matte 5m	Polyester	Clear	3	2	Thermal
Instaheild Velvet Matte	Polyester	Clear	3	1.2	Acrylic
Instashield Dry Erase	Polypropylene	Clear	2	1.2	Acrylic
Instashield FG Floorgraphic	Vinyl	Clear	5	1.2	Acrylic
Instashield UV Gloss 1.5mil	Polyester	Clear	1.5m	1	Solvent Acrylic
Instashield UV Gloss 3.0m	3	Clear	1.2	3	Solvent Acrylic
Instashield UV Gloss E	Vinyl	Clear	3.4	1.2	Acrylic
Instashield UV Gloss Wide	Vinyl	Clear	3.5	1.2	Solvent Acrylic
Instashield UV Lustre	Vinyl	Clear	3.5	1.2	Solvent Acrylic
Instashield UV Lustre E	Vinyl	Clear	3.5	1.2	Acrylic
Instashield UV Matte	Vinyl	Clear	3.5	1.2	Solvent Acrylic
Instashield UV Matte E	Vinyl	Clear	3.5	1.2	Acrylic
Instashield UV Velvet Polycarbonate	Polycarbonate	Clear	5, 10 & 15	1.2	Solvent Acrylic
Premium Cast Clear Gloss	Cast Vinyl	Clear	2	1.2	Solvent Acrylic
Premium Cast Clear Lustre	Cast Vinyl	Clear	2	1.2	Solvent Acrylic
Premium Cast Clear Matte	Cast Vinyl	Clear	2	1.2	Solvent Acrylic
Quality Value Gloss	Vinyl	Clear	3.5	1.2	Solvent Acrylic
Quality Value Lustre	Vinyl	Clear	3.5	1.2	Solvent Acrylic
Quality Value Matte	Vinyl	Clear	3.5	1.2	Solvent Acrylic
Que Media Inc., 888-763-3421, www.MyPRINTResource.com/10007571					
Gloss Laminate (LAMGL)	PVC	clear	4	4	Permanent Solvent
Matte Laminate (LAMMT)	PVC	clear	4	4	Permanent Solvent
Satin Laminate (LAMST)	PVC	clear	4	4	Permanent Solvent
Textured Matte Laminate (LAMTXT)	PVC	clear	6	6	Permanent Solvent
Remington Laminations Inc., 877-317-1716, www.MyPRINTResource.com/10007667					
Graffit Free laminate	Anti-Graffiti laminate	PCTFE	clear	1	Solvent Acrylic PSA
Oxo-Biodegradable Laminating Film	Bioriented Polypropylene film	Clear	1.2	1.2	Thermal extrusion coated eva
RemiBacker MB	Paper/poly	White	10	10	Thermal UV resistant coextrusion
RemiBlocker-10 LT	Polyester	White	10	10	Thermal coextrusion
RemiChrome-3	Polyester	Clear	3	4	Solvent Acrylic PSA
RemiCrystal-10	Rigid PVC	Clear	9	10.8	Solvent Acrylic PSA
RemiCrystal-3	Calendered PVC	Clear	3	3	Solvent Acrylic PSA
RemiCrystal-5	Calendered PVC	Clear	5	6.5	Solvent Acrylic PSA

RESOURCE CHART

Release Liner	Activation Temp (°F)	Width(s)	Core Size (inches)	Finish	Ink Compatibility
	185-195	26 to 76	3	Gloss	All Types
	195-205	25 to 76	3	Gloss	All Types
	185-195	26 to 62	3	Matte	All Types
	185-195	25 to 76	3	Satin	All Types
	195-205	25 to 76	3	Satin	All Types
	185-195	38 to 51	3	Matte	All Types
	195-205	38 to 51	3	Matte	All Types
	175-185	41 to 51	3	Gloss	All Types
	175-185	38 to 51	3	Luster	All Types
	175-185	38 to 51	3	Matte	All Types
	175-185	51	3	Matte	All Types
	175-185	38 to 51	3	Textured	All Types
Film	PSA	38 to 51	3.00	Textured	All Types
Film	PSA	38 to 54	3.00	Textured	All Types
Film	PSA	38 to 61	3.00	Luster	All Types
	210-220	25 to 51	3	Textured	All Types
	195-205	25 to 51	3	Textured	All Types
	195-200	25 to 76	3	Textured	All Types
	185-195	38 to 51	3	Gloss	All Types
	185-195	12 to 55	3	Gloss	All Types
	210-220	12 to 62	3	Gloss	All Types
	185-195	12 to 61	3	Gloss	All Types
	195-205	12 to 62	3	Gloss	All Types
	185-195	12 to 62	3	Matte	All Types
	185-195	12 to 61	3	Satin	All Types
	210-220	25 to 55	3	Luster	All Types
	195-205	25 to 51	3	Luster	All Types
	210-220	12 to 51	3	Matte	All Types
	195-205	25 to 51	3	Matte	All Types
Film	PSA	38 to 51	3	Matte	All Types
PE Coated Kraft Paper	PSA	25 to 54	3	Gloss	All Types
Film	PSA	25 to 54	3	Textured	All Types
Film	PSA	25 to 51	3	Gloss	All Types
	PSA	25 to 61	3	Gloss	All Types
PE Coated Kraft Paper	PSA	25 to 54	3	Gloss	All Types
PE Coated Kraft Paper	PSA	79	3	Gloss	All Types
PE Coated Kraft Paper	PSA	25 to 62	3	Luster	All Types
PE Coated Kraft Paper	PSA	25 to 61	3	Luster	All Types
PE Coated Kraft Paper	PSA	25 to 79	3	Matte	All Types
PE Coated Kraft Paper	PSA	25 to 61	3	Matte	All Types
Film	PSA	38 to 60.5	3	Textured	All Types
PE Coated Kraft Paper	PSA	48 to 60	3	Gloss	All Types
PE Coated Kraft Paper	PSA	48 to 60	3	Luster	All Types
PE Coated Kraft Paper	PSA	48 to 60	3	Matte	All Types
PE Coated Kraft Paper	PSA	38 to 60	3	Gloss	All Types
PE Coated Kraft Paper	PSA	38 to 61	3	Luster	All Types
PE Coated Kraft Paper	PSA	38 to 61	3	Matte	All Types
PE Coated Paper	PSA	38, 51, 61	3	Gloss	Universal (Solvent Direct Print Capable)
PE Coated Paper	PSA	38, 51, 61	3	Matte	Universal (Solvent Direct Print Capable)
PE Coated Paper	PSA	38, 51, 61	3	Satin	Universal (Solvent Direct Print Capable)
PE Coated Paper	PSA	38, 51, 61	3	Textured	Universal (Solvent Direct Print Capable)
Solvent Acrylic PSA	42 lb. PWF	54	3	Gloss	All Types
None	250 F	12,27.5,38,43,51,55	3	Gloss/Matte	Offset
None	215 F	38, 51	3	White backer	All Types
None	215 F	38, 51	3	White opaque	All Types
siliconized Polyester		25,38,41,51,54	3	Gloss	All Types
siliconized Polyester		38,41,51,54	3	Textured Matte	All Types
42 lb. Poly flat white		38,41,51,54	3	Textured	All Types
siliconized Polyester		25,38,41,51,54	3	Textured Matte	All Types

2012 OVERLAMINATE

Product Name	Film Type	Color	Film Thickness (mil)	Film + Adhesive Thickeness (mil)	Adhesive Type
RemiErase 1.7	Polyester	clear	1.7	1.7	thermal coextrusion
RemiFrost-3	calendered PVC	clear	3.2	4.3	Solvent Acrylic PSA
RemiGloss 1.7	Polyester	clear	1.7	1.7	thermal coextrusion
RemiGloss-10 LT	Polyester	clear	10	10	thermal UV resistant coextrusion
RemiGloss-3 LT	Polyester	clear	3	3	thermal UV resistant coextrusion
RemiGloss-5 LT	Polyester	clear	5	5	thermal UV resistant coextrusion
RemiGlossy-12	PVC	clear	12	14	Solvent Acrylic PSA
RemiGlossy-4	calendered PVC	clear	4	5	Solvent Acrylic PSA
RemiLustre-10 LT HC	Polyester	clear	10	10	thermal UV resistant coextrusion
RemiLustre-3	calendered PVC	clear	3.2	4.3	Solvent Acrylic PSA
RemiLustre-3 ECO	calendered PVC	clear	3	4	aqueus acrylic PSA
RemiLustre-5 LT HC	Polyester	clear	5	5	thermal UV resistant coextrusion
RemiMatte-1	Polyester	clear	1	2	Solvent Acrylic PSA
RemiMatte-3	Polyester	clear	3	3	thermal UV resistant coextrusion
RemiSatin-5 LT	Polyester	clear	5	5	thermal UV resistant coextrusion
RemiTex-6 LT	Polyester	clear	6	6	thermal UV resistant coextrusion
RemiWrite-1 Matte	polypropylene	clear	1.2	1.2	thermal coextrusion
RemiWrite-2	polypropylene	clear	2	3	Solvent Acrylic PSA
RemSatin-3 LT	Polyester	clear	3	3	thermal UV resistant coextrusion
Soft Touch®Matte laminating film	Bioriented Polypropylene film	clear Matte	1.2	1.2	thermal extrusion coated eva
Soft Touch®Matte Metallized laminating film	Bioriented Polypropylene film	silver/metallized	1.2	1.2	thermal extrusion coated eva
Royal Sovereign International Inc., 800-397-1025, www.MyPrintResource.com/10007790					
Lomel	Polyester	Clear	1, 2	3, 5	Thermal
PrintPro 4.5 UV	Vinyl	Clear	3.5	4.5	PSA - Solvent Acrylic
Royalam	Polyester	Clear	Various	Up to 10	Thermal
Royal FOTO FLEX	Vinyl with Polyester carrier	Clear	3.2	4.4	Thermal

RESOURCE CHART

Release Liner	Activation Temp (°F)	Width(s)	Core Size (inches)	Finish	Ink Compatibility
None	215 F	38, 43, 51, 55	3	Gloss	All Types
42 lb. Poly flat white		25,33,41,43,51,54,61	3	Matte	All Types
None	215 F	25,38,43,51,55,60	3	Gloss	All Types
None	210 F	25,38,43,51,55,61	3	Gloss	All Types
None	195 F	25,38,43,51,55,61	3	Gloss	All Types
None	195 F	25,38,43,51,55,61	3	Gloss	All Types
78 lb. Poly flat white		26.5, 53	3	Gloss	All Types
62 lb. Poly flat white		25,38,41,51,54,61	3	Gloss	All Types
None	210 F	38, 51	3	hard coat Matte	All Types
42 lb. Poly flat white		25,33,41,43,51,54,61	3	luster	All Types
44 lb. poly flat white		38,51	3	luster	All Types
None	195 F	38, 51, 55	3	hard coat Matte	All Types
42 lb. Poly flat white		60	3	Matte	All Types
None	195 F	25,38,43,51,55,61	3	Matte	All Types
None	195 F	25,38,43,51,55,61	3	Satin	All Types
None	195 F	38, 51, 55	3	textured Satin	All Types
None	215 F	38,51	3	Matte	All Types
42 lb. Poly flat white		25,38,41,51,54	3	Gloss	All Types
None	195 F	25,38,43,51,55,61	3	Satin	All Types
None	250 F	12,27.5,38,43,51,55	3	Matte	Offset
None	250 F	12,27.5,38,43,51,55	3	silver	Offset
No	194	Up to 55	3	Gloss, Matte	
Yes	68-122	30,38,51,54,60	3	Gloss, Luster, Matte(Sand)	
No	235	Up to 55	1, 3	Gloss, Matte, Luster	
No	220	38, 51	3	Matte-Sand	